



Instant Dry Photo Satin 195 g/m² Inkjet Paper

A true PE coated microporous Satin paper designed for use with both DYE and PIGMENT based PIEZO & THERMAL printers. This heavyweight paper is instant dry and excellent for laminating.

Product Specification

Thickness μm 188 \pm 5
Weight g/m² 190 \pm 7
PE-weight VS g/m² 18 \pm 2
PE-weight RS g/m² 26 \pm 2
Curl, 23°, 50% mm 0 \pm 8
Gloss (Dr. Lange) 60° % 25 \pm 5
Colour Hunter UVI L 92.5 \pm 0.5
a -0.3 \pm 0.5
b -4.1 \pm 0.8
CIE Whiteness D65 107
Brightness D65 90

Roll widths 91.4, 106.7, 111.8, 127.0, 152.4 cm

Roll lengths 30 m standard

Applications Photography, Posters, Graphic Art, Reproduction, POS Signage, Exhibition graphics, Desktop Publishing

Strengths Instant-dry, good colour density, excellent image sharpness, smudge resistant, universal compatibility
5760 dpi resolution possible Best results at 1440 dpi

Laminability Hot & Cold

Compatible Printers

Small Format

HP Photosmart/Deskjet/Office Series; Canon BJC/S & i Series; Epson Stylus Color/Photo/C Series, Epson Stylus 2000P/2100; Lexmark all models

Large Format

HP 5000/5500 (Dye/UV Inks)

HP 500/800

HP 1050/1055

HP 2000/3000 (Dye/UV Inks)

HP 10/20/50/100/120/430/450/488

Canon W 2200/7200/7250, Canon BJ-W 3000/3050

Encad all models (GS/GS+ (Dye) Inks), Encad all models (GO/GO+ (UV) Inks)

Epson 3000/5000 (Dye Inks), Epson 5500 (UV Inks), Epson 7000/9000/10000 (Dye Inks), Epson

7500/9500/10000CF (UV Inks), Epson 7600/9600/10600 (Ultrachrome Inks)

Agfa Sherpa/Grand Sherpa

Colorspan X-II /X-12/ Esprit (EnduraChrome Dye Inks), Colorspan X-II /X-12/ Esprit (PermaChrome UVInks)

Roland FJ Series

Mutoh RJ Series

OCE CS Series

Mimaki JV Series

Directions for use

Store paper only in original boxes, out of direct sunlight under normal climatic conditions (23°, 50% RH).

You can improve results by using the best possible printer settings!

Important Notice

The information above is based upon data we believe to be reliable. Values are intended as a source of information and are given without guarantee and do not constitute a warranty of any kind. Purchasers should determine the suitability of any mediaTech product independently prior to application to their specific purpose.

Atech Ltd., 15, Little Mundells, Welwyn Garden City, Herts. AL7 1EW.

Tel: +44 (0) 1707 334422

Fax: +44 (0) 1707 326600